

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

8733.20050

First Inventor or Application Identifier

Youn Gyoung CHANG et al.

Title

THIN FILM TRANSISTOR TYPE OPTICAL DETECTING SENSOR

PTO
1999/12/20
1999/12/20



12/20/99

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

- ☒ Fee Transmittal Form (e.g. PTO/SB/17)
(Submit an original and a duplicate for fee processing)

2. ☒ Specification

Total Pages **13**

3. ☒ Drawing(s) (35 U.S.C. 113) Total Sheets

4

4. ☒ Oath or Declaration

Total Pages **1**

- a. ☐ Newly executed (original or copy)
b. ☐ Copy from a prior application (37 C.F.R. §1.63(d))
(for continuation/divisional with box 15 completed)
i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named
in the prior application, see 37 C.F.R. §1.63(d)(2) and
1.33(b).

5. ☐ **Incorporation By Reference** (usable if box 4B is checked)
The entire disclosure of the prior application, from which a copy of the
oath or declaration is supplied under Box 4B, is considered to be part
of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

ACCOMPANYING APPLICATION PARTS

6. ☒ Assignment Papers (cover sheet & document(s))
7. ☐ 37 C.F.R. §3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
8. ☐ English Translation Document (if applicable)
9. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
10. ☐ Preliminary Amendment
11. ☒ White Advance Serial No. Postcard
12. ☐ Small Entity Statement(s) ☐ Statement filed in prior application. Status still proper and desired.
13. ☒ **Certified Copy of Priority Document(s)**
(if foreign priority is claimed)
14. ☐ Other:

15. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below:

- ☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application no.:
Prior application information: Examiner: Group Art Unit:

16. Amend the specification by inserting before the first line the sentence:

- ☐ This application is a ☐ Continuation ☐ Division ☐ Continuation-in-part (CIP)
of application Serial No. Filed on
☐ This application claims priority of provisional application Serial No. Filed

17. CORRESPONDENCE ADDRESS

LONG ALDRIDGE & NORMAN LLP
701 Pennsylvania Avenue, N.W.
Washington, D.C. 20004
(202) 624-1200
FACSIMILE: (202) 624-1298

Name:	Kenneth D. Springer	Registration No.:	39,843
Signature:		Date:	20 December 1999
Name:		Registration No.:	

UNITED STATES PATENT APPLICATION

OF

YOUN-GYOUNG CHANG

JEONG-HYUN KIM

JAE-KYUN LEE

FOR

THIN FILM TRANSISTOR TYPE OPTICAL DETECTING SENSOR

0346991 121099
550221 1969460

This application claims the benefit of Korean Patent Application No. 99-17169, filed on May 13, 1999, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an optical detecting sensor, and more particularly, to a thin film transistor (TFT) type optical detecting sensor that has a sensor TFT, and a switching TFT.

Discussion of the Related Art

10 The TFT type optical detecting sensor detects an image of an object by producing a detecting current in response to light reflected from the object. The sensor is comprised of a light source, a window which transmits light from the light source to the object, a sensor TFT which generates an optical current in accordance to the amount of the light reflected from the object, a storage capacitor which stores charges of the optical current generated in the sensor
15 TFT, and a switching TFT which controls the release of charges of the storage capacitor to an external circuit.

Since the sensor TFT and the switch TFT are comprised of similar elements, in making the detecting sensor, the active layers for the sensor TFT and the switching TFT are preferably deposited and patterned at the same time. The active layer for the sensor TFT
20 should be chosen among the materials that are sensitive to light and active in converting light into current. Also the active layer of the switching TFT should be proper for the switching operation. Thus, to satisfy both conditions, the active layer for the TFTs is preferably an amorphous silicon layer having hydrogen (a-Si:H, herein after referred as "amorphous silicon layer").

Since the switching TFT is operated by a voltage applied to a gate of the switching TFT, not by the light, the active layer of the switching TFT should be shielded from light, whereas the active layer of the sensor TFT generates optical current by the incident light reflected from the object.

5 Fig. 1 is a schematic sectional view of a conventional optical detecting sensor, which can explain a manufacturing process.

First, on a transparent and insulating substrate 10, regions for a window, a sensor TFT, a storage capacitor, and a switching TFT should be defined as the areas "D", "C", "B" and "A", respectively, in advance.

10 A first conducting metal layer is deposited on the substrate 10 and patterned into a sensor gate electrode 11, a first capacitor electrode 13 and a switch gate electrode 15 in the corresponding areas, respectively.

A first insulating layer is deposited on the substrate 10 while covering the patterned conducting metal layer.

15 An amorphous silicon layer and an n+ amorphous silicon layer are deposited in succession on the first insulating layer to form sensor and switch active layers 19 and 21 and ohmic contact layers 23 and 25 for the corresponding active layers 19 and 21, respectively.

A second conducting metal layer is deposited on the first insulating layer and patterned into sensor source and drain electrodes 27a and 27b, a second capacitor electrode 29
20 and switch source and drain electrodes 31a and 31b. The second conducting metal layer may be made of a general non-transparent metal or a transparent conducting material, for example, indium tin oxide.

A second insulating layer 33 is deposited on the second conducting metal layer and the exposed portion of the active layers 19 and 21. Then a light shielding layer 35 is formed on the second insulating layer 33 over the switch active layer 21.

The contact portion between switch drain electrode 31b and the switch active layer 21 is shown in detail in Fig. 2, which is an enlarged view of portion "J" of Fig. 1.

The upper portion of the switch active layer indirectly contacts the switch drain electrode 31b through the ohmic contact layer 25 that restricts the hole current flow, whereas the side portion "w" of the switch active layer 21 directly contacts the switch drain electrode 31b. Since there is no ohmic contact layer in the side contact area "w" of the switch active layer 21, the leakage current to the switch drain electrode 31b is bigger than in the upper contact portion of the switch active layer 21, resulting in an adverse affect on the operation characteristics of the switch TFT.

Fig. 3 shows the relationship between gate voltage V_{G2} for switching TFTs having drain electrodes made of different materials and drain current I_D . If the drain electrode is made of transparent conducting material, as illustrated in solid line 36, the leakage current (or off-current) and the on-current are low, since resistance of the transparent conducting material is relatively high, which means that there is a small current gap between negative and positive voltage of gate electrode. If the drain electrode is made of a non-transparent metal, as illustrated in the dot-dash line 34, both the off-current and the on-current are relatively high, also resulting in a small gap between the off-current and on-current.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to an optical detecting sensor having a switch TFT with reduced off-current and increased on-current that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

5 An object of the present invention is to provide an optical detecting sensor having a switch with good operation characteristics.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objective and other advantages of the invention will be realized
10 and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, an optical detecting sensor includes a sensor thin film transistor (TFT) generating optical current by incident light reflected from an
15 object; a storage capacitor storing charges of the optical current generated in the sensor thin film transistor; and a switching TFT controlling the release of the stored charges of the storage capacitor to an external circuit for display of an image of the object, the switching TFT having dual-layered source and drain electrodes of transparent conducting material and metal material, an active layer and a gate electrode.

20 It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWING

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

Fig. 1 is a sectional view of an optical detecting sensor according to the prior art;

Fig. 2 is an enlarged view of portion "J" of Fig. 1;

Fig. 3 is a graph illustrating the relationship between gate voltage V_G and drain current I_D for a switching TFT with a non-transparent metal drain electrode and for a switching TFT with a transparent conducting material drain electrode;

Figs. 4a to 4c are sectional views illustrating a process of manufacturing an optical detecting sensor according to the present invention;

Fig. 5 is an enlarged view of portion "P" of Fig. 4a; and

Fig. 6 is a graph illustrating the relationship between gate voltage V_G and drain current I_D , a switching TFT with a non-transparent metal drain electrode, a switching TFT with a transparent conducting material drain electrode, and a switching TFT having the drain electrode according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to a preferred embodiment of the present invention, an example of which is illustrated in the accompanying drawings.

Figs. 4a to 4c illustrate a process of manufacturing an optical detecting sensor according to an embodiment of the present invention. On a transparent substrate 110, regions

for a switching TFT, a storage capacitor, a sensor TFT, and a window are defined as "E", "F",
"G", and "H", respectively. A conducting metal layer is deposited on the substrate 110 and
patterned into a sensor gate 111, a first capacitor electrode 113, and a switch gate 115 in the
corresponding regions, as shown in Fig. 4a. The conducting metal is preferably selected from
5 the group consisting of molybdenum (Mo), tungsten (W) and aluminum (Al).

As shown in Fig. 4b, a first insulating layer 117, which is preferably one of the group
consisting of aluminum oxide (Al_2O_3), silicon oxide (SiO_2) and tantalum oxide (TaO_5), is
deposited on the substrate 121 while covering the switch gate 115, the first capacitor
electrode 113 and the sensor gate 111. An amorphous silicon layer and an n+ amorphous
10 layer are deposited on the first insulating layer 117 in succession to form switch and sensor
active layers 121 and 119, and switch and sensor ohmic contact layers 125 and 123 over
switch and sensor gates 115 and 111, respectively. Switch and sensor active layers 121 and
119 are preferably smaller than the switch and sensor gates 115 and 111, respectively, in
order to protect the active layers 121 and 119 from the light of a light source (not shown)
15 under the substrate 110. A transparent conducting material is deposited thereon to form
switch source and drain electrodes 129a and 129b, a second capacitor electrode 131 and
sensor source and drain electrodes 127a and 127b. In the thin film transistor optical detecting
sensor, since it is desirable that light from the light source positioned under the substrate 110
should be transmitted to an object over the substrate through the substrate 110, especially
20 through the window area "H" as much as possible, a transparent conducting material such as
indium tin oxide is used.

Also, the switch source and drain electrodes 129a and 129b do not cover the whole
ohmic contact layers 125, as shown in Fig. 4b, and each ohmic contact layer 125a and 125b
for switch source and drain electrodes 129a and 129b has an exposed portion " ΔL ".

Referring to Fig. 4c, subsidiary switch source and drain electrodes 133a and 133b made of a non-transparent metal are formed on the switch source and drain electrodes 129a and 129b while contacting the exposed portions "ΔL" of the ohmic contact layers 125a and 125b, respectively. Thus, the switch drain and source electrodes have a dual layered structure.

5 The non-transparent metal is selected from the group consisting of tungsten, molybdenum and chrome, each of which has a lower contact resistance than the transparent conducting material such as indium tin oxide.

10 The second insulating layer 135 is deposited on the whole surface of the substrate 110, after forming the subsidiary switch source and drain electrodes 133a and 133b. A light shielding layer is formed thereon over the switch active layer 121.

Referring to Fig. 5 which is an enlarged view of portion "P" of Fig. 4c, the contact structure between the ohmic contact layer 125b and the dual layered drain electrode is explained in detail. For an optical detecting sensor, the drain and source electrodes of the switching TFT should employ the transparent conducting material. But according to the embodiment of the invention, the drain and source electrodes have a dual layered structure of transparent material electrode 129b(129a) and non-transparent metal electrode 133b(133a). The transparent material can function as a hole barrier layer between the semiconductor layer and the source and/or drain electrode(s). Thus, the OFF-current or leakage current can be reduced by adopting the transparent electrode 129b(129a), while the ON-current can be maintained by the non-transparent metal electrode 133b(133a).

Fig. 6 is a transfer curve which shows the relationship between gate voltage V_G and drain current I_D for switching TFTs whose drain electrode is made of a non-transparent metal (dot-dashed line), a transparent conducting material (dashed line) and the dual-layered drain electrode (solid line) according to the present invention.

5 The dual-layered drain electrode 45 according to the present invention has a characteristic such that in the negative gate voltage region, the off-current or leakage current, which is desired to be as low as possible, is almost the same as that of the transparent conducting material drain electrode 43, whereas the on-current, which is desired to be as high as possible, is almost the same as that of the non-transparent metal drain electrode 41.

Therefore, since the thin film transistor optical detecting sensor according to the present invention has a switching thin film transistor having dual-layered source/drain electrodes, the switching characteristics can be improved.

10 It will be apparent to those skilled in the art that various modifications and variation can be made in the thin film transistor type optical detecting sensor of the present invention without departing from the scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1 1. An optical detecting sensor, comprising:
2 a sensor thin film transistor (TFT) generating optical current by incident light
3 reflected from an object;
4 a storage capacitor storing charges of the optical current generated in the sensor thin
5 film transistor; and
6 a switching TFT controlling a release of the stored charges of the storage capacitor to
7 an external circuit for display of an image of the object, the switching TFT having dual-
8 layered source and drain electrodes of a transparent conducting material and a metal material,
9 an active layer and a gate electrode.

1 2. An optical detecting sensor according to claim 1, wherein the metal for the dual-
2 layered drain and source electrodes is a substantially non-transparent metal material.

1 3. An optical detecting sensor according to claim 1, wherein the metal for the dual-
2 layered drain and source electrodes is selected from a group consisting of tungsten, chrome
3 and molybdenum.

1 4. An optical detecting sensor according to claim 1, wherein the transparent conducting
2 material is indium tin oxide.

1 5. An optical detecting sensor according to claim 1, wherein the dual-layered source and
2 drain electrodes each comprise a transparent conducting material layer residing on a metal
3 material layer.

1 6. An optical detecting sensor according to claim 5, wherein the metal material is a
2 substantially non-transparent metal material.

1 7. An optical detecting sensor according to claim 1, wherein said switching thin film
2 transistor further comprises an ohmic contact layer on the active layer through which the
3 dual-layered drain and source electrodes contact the active layer.

1 8. An optical detecting sensor according to claim 7, wherein the dual-layered source and
2 drain electrodes each comprise a transparent conducting material layer residing on a metal
3 material layer.

1 9. An optical detecting sensor according to claim 8, wherein the metal material is a
2 substantially non-transparent metal material

1 10. An optical detecting sensor according to claim 8, the transparent conducting material
2 layer and the metal material layer each contact the ohmic contact layer.

1 11. An optical detecting sensor according to claim 10, wherein the transparent conducting
2 material layer also contacts the active layer.

1 12. An optical detecting sensor according to claim 11, wherein the transparent conducting
2 material layer contacts the active layer at an edge thereof.

1 13. A thin film transistor (TFT) image sensor, comprising:
2 a sensor TFT having a gate electrode and spaced apart first and second electrodes;
3 a switching TFT comprising,
4 a gate electrode,
5 an insulating layer formed on the gate electrode,
6 a semiconductor layer formed on the insulating layer above the gate electrode,
7 spaced apart first and second electrodes formed on the semiconductor layer
8 and defining a channel region therebetween in said semiconductor layer, and
9 a hole barrier layer between the semiconductor layer and at least one of the
10 first and second electrodes; and
11 a storage capacitor having a first electrode and a second electrode, the second
12 electrode of the storage capacitor being connected to the first electrode of the sensor TFT and
13 the second electrode of the switching TFT.

1 14. A thin film transistor (TFT) formed on a substrate, comprising:
2 a gate electrode formed on the substrate;
3 an insulating layer formed on the gate electrode;
4 a semiconductor layer formed on the insulating layer above the gate electrode;
5 source and drain electrodes spaced apart and formed on the semiconductor layer and
6 defining a channel region therebetween in said semiconductor layer; and
7 a hole barrier layer between the semiconductor layer and at least one of the source and
8 drain electrodes.

ABSTRACT OF THE DISCLOSURE

An optical detecting sensor includes a sensor thin film transistor generating an optical current in response to incident light reflected from an object; a storage capacitor storing charges of the optical current generated in the sensor thin film transistor; and a switch thin film transistor controlling release of the stored charges of the storage capacitor to an outer circuit for display of image of the object, having dual-layered source and drain electrodes of transparent conducting material and metal material, an active layer and a gate electrode. The switch thin film transistor further includes an ohmic contact layer on the active layer through which the dual-layered drain and source electrodes contact the active layer.

046561 12099




FIG. 1




FIG. 2




FIG. 3




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 5




FIG. 6

**DECLARATION
and POWER OF ATTORNEY**

As a below named inventor, I declare that the information given herein is true, that I believe that I am the original, first and sole inventor if only one name is listed at 1 below, or a joint inventor if plural inventors are named below at 1-4, of the invention entitled Thin Film Transistor Type Optical Detecting Sensor which is described and claimed in: ☒ the attached specification, or ☐ the specification in Application No. _____ filed _____

☐ as amended on _____ (if applicable),

and for which a patent is sought, and that my residence, post office address and citizenship are as stated below next to my name.

I acknowledge my duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING Month Day Year	PRIORITY CLAIMED UNDER 35 U.S.C. 119
KOREA	99-17169	May 13, 1999	YES

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

(Application Number) (Filing Date) (Status)

POWER OF ATTORNEY As a named inventor, I hereby appoint the following attorney(s) and/or Agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith

STEVEN B. KELBER, Reg. No. 30,073, MARC R. LABGOLD, Ph.D., Reg. No. 34,651, SONG K. JUNG, Reg. No. 35,210, SHARON E. CRANE, Ph.D., Reg. No. 36,113, CATHERINE BAX RICHARDSON, Reg. No. 39,007, KENNETH D. SPRINGER, Reg. No. 39,843, JAMES M. HEINTZ, Reg. No. 41,828, and AMY L. MILLER, Reg. No. 43,804

Send correspondence to

Long Aldridge & Norman LLP
701 Pennsylvania Avenue, N.W.
Suite 600
Washington, D.C. 20004

Direct telephone calls to:

Song K. Jung
(202) 624 1250

(Please print)

1	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence CITY	STATE OR COUNTRY
		CHANG	Youn	Gyoung	Kunpo	KOREA
		Post Office Address 958-201 Baekdutsung-Apt, Sanbon-dong, Kunpo, Kyonggi-do, KOREA				COUNTRY OF CITIZENSHIP KOREA
2	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence CITY	STATE OR COUNTRY
		KIM	Jeong	Hyun	Kunpo	KOREA
		Post Office Address 650-1101 Sejong-Apt, 1145 Kwangjeong-dong, Kunpo, Kyonggi-do, KOREA				COUNTRY OF CITIZENSHIP KOREA
3	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence CITY	STATE OR COUNTRY
		LEE	Jae	Kyun	Anyang	KOREA
		Post Office Address 941-4 Hoge-dong, Tongan-ku, Anyang, Kyonggi-do, KOREA				COUNTRY OF CITIZENSHIP KOREA
4	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence CITY	STATE OR COUNTRY
		Post Office Address				COUNTRY OF CITIZENSHIP

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon

Signature of INVENTOR 1	<i>Youn Gyoung Chang</i>	Signature of INVENTOR 2	<i>Jeonghyun Kim</i>
DATE	<i>Nov 24, 1999</i>	DATE	<i>Nov 24, 1999</i>
Signature of INVENTOR 3	<i>Joe Kyun Lee</i>	Signature of INVENTOR 4	
DATE:	<i>Nov 29, 1999</i>	DATE	